



**HR32 Marlin  
BT SD**  
Handheld Scanners

## Features

### Mega Pixel Scanning Technology

Equipped with a megapixel barcode scanner, the HR32 Marlin BT SD reads virtually all 1D or 2D barcodes in any condition. It has a better reading performance on reading long or truncated 1D codes or larger and more high-density 2D codes.

### Perfected for POS

The HR32 Marlin BT SD has a stand design for hands-free scanning, especially ideal for POS applications. Users can process smaller items without having to pick up the scanner. The scanner can then be picked up to use for more oversized items without dealing with cables.

### JPOS and OPOS Driver Support

When in HID-POS or Newland CDC mode, JPOS and OPOS drivers are supported via the dongle directly or the dongle, stand + USB cable combination.

### Supports the Workload

The 2400mAh battery, combined with the low power consumption of the HR32 Marlin BT SD and lower power Bluetooth 5.0, means a full charge can last over 12 hours. A charge from empty to full takes less than 4 hours.

### Fit for the job

With a 1.5m drop and IP52 rating, the HR32 Marlin BT SD can take a tumble from a high countertop or workbench onto hard floors with no problem. The IP52 is a high enough sealing for dirty and damp environments.

### Flexible Bluetooth Options

The HR32 Marlin BT SD has 3 Bluetooth options. When the dongle and charging station is connected, the scanner transmits data via the USB cable to the host. The dongle can also be removed and used in a spare USB port, and the Bluetooth on the scanner can be paired with a 3rd party Bluetooth on a host.

## Suggested industries



Retail



Warehousing



Hospitality



Finance



Healthcare



# HR32 Marlin BT SD Technical specifications

## Data Capture

1D	EAN-8, EAN-13, UPC-E, UPC-A, Code128, Coupon, UCC/EAN128, CodaBar, I2Of5, Febraban, ITF14, ITF6, Matrix 25, Code39, Code93, ISSN, ISBN, Industrial 25, Standard 25, China Post 25, Plessey, Code 11, MSI Plessey, UCC/EAN Composite, GS1 Databar, Code 49, Code 16K, AIM 128, ISBT 128.
2D	PDF417, Micro PDF417, QR Code, Micro QR Code, Aztec, Data Matrix, Chinese Sensible Code, Maxicode, Code One.
Image Sensor	CMOS 1280 x 800
Aiming	Green LED
Illumination	White LED & Red LED
Depth of Field EAN 13 (13mil)	50-495mm
Depth of Field Code 39 (5mil)	85-220mm
Depth of Field PDF417 (6.67mil)	70-215mm
Depth of Field DataMatrix (10mil)	50-220mm
Depth of Field QR (15mil)	20-325mm
Field of View Horizontal	39°
Field of View Vertical	24°
Scan Angle Roll	360°
Scan Angle Pitch	±55°
Scan Angle Skew	±55°
Minimal Print Contrast	25%

## Performance

Memory Flash	1MB e.g. ≥15000 pieces of Code 128 (20 byte of each Code 128)
--------------	---

## Physical

Battery Type	2400 mAh lithium-ion battery
Current @ 5VDC Operating	5VDC±5%
Dimensions (mm)	Scanner: 113.5(W) x73.3(D) x159.0(H) mm
Expected Battery Life	≥12 hours of continuous operation (scan once per 6 seconds)
Expected Charge Time	4 hours (with power adapter)
Interfaces	USB
Notifications	Beep, LED indicator
Weight	Scanner: 217g

## Wireless

Radio Technology	Bluetooth 5.0
Wireless Distance (max.)	≥50m/164ft (direct line of sight in open air)
Communication Modes	Synchronous, asynchronous and batch modes

## Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved

# HR32 Marlin BT SD Technical specifications

Humidity	5%~95% (non-condensing)
Electro Static Discharge (ESD)	±8KV (air discharge); ±4KV (direct discharge)
Drop	Scanner: 1.5m Cradle: 1.2 m
IP Rating	IP52

## Certifications

Hardware	FCC Part15 Class B, CE EMC Class B, RoHS
----------	--

## Warranty

Standard	3 years
----------	---------

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Feel free to contact us or a partner near you

visit [newland-id.com/partners](http://newland-id.com/partners)

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved